

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) **EP 1 429 531 A1**

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
16.06.2004 Bulletin 2004/25

(51) Int Cl.⁷: **H04N 1/00, H04N 7/14**

(21) Application number: **02027796.8**

(22) Date of filing: **12.12.2002**

(84) Designated Contracting States:
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
IE IT LI LU MC NL PT SE SI SK TR
Designated Extension States:
AL LT LV MK RO SI

(72) Inventor: **Schack, Goran**
296 33 Åhus (SE)

(74) Representative: **Dahnér, Christer et al**
Ström & Gulliksson IP AB,
Box 7086
103 87 Stockholm (SE)

(71) Applicant: **Sony Ericsson Mobile**
Communications AB
221 88 Lund (SE)

(54) **Portable communication device provided with camera**

(57) The present invention relates to a portable communication device (10) having a rotatable built-in camera.




Fig. 3

EP 1 429 531 A1

BEST AVAILABLE COPY

Description

TECHNICAL FIELD OF THE INVENTION

[0001] The present invention relates to a portable communication device, and more particularly, to a portable communication device provided with a camera.

DESCRIPTION OF RELATED ART

[0002] Future portable communication devices, for instance cellular phones, will need to be capable of sending multimedia messages from phone to phone and phone to internet and vice versa. For instance, a photo taken by the portable communication device having access to a camera can be sent off as an e-mail or MMS, or could be used for customizing a display appearance of the phone. An integrated or an accessory digital camera is, therefore, a useful additional tool in a portable communication device such as a cellular phone.

[0003] Cameras in known cellular phones are either fixed in different position or could be rotated either by means of a hinge mechanism or in an upper end of the phone. An example of this technique could for instance be found in KR-A-313 146 (Samsung), describing a camera lens in a folder-type cellular phone.

[0004] When all components in the portable communication device and the device itself become smaller and smaller, it is very difficult to find space for a built-in rotatable camera without extending the device in size or provide the camera as an connectable accessory.

[0005] There is therefore a need for a portable communication device, having a rotatable camera, which does not suffer from severe increase in size due to the camera.

SUMMARY OF THE INVENTION

[0006] The present invention is directed towards solving the problem of providing a portable communication device with a camera, in particular a built-in rotatable camera that does not require much space of the device.

[0007] Thus, one object of the present invention is to provide a portable communication device having a camera solving the problem stated above.

[0008] Typically, the basic parts of a digital camera of today are: a chipset, a camera sensor and a lens system, of which the lens system has already been described above. Typically, a complete camera of today comprises the chipset and camera sensor in the form of a square shaped module having a cylindrical lens system provided thereon. In a small sized product, this is not optimal for a rotatable camera mounted in a cylinder with the camera lens axis perpendicular to the cylinder axis, since the dimension of the square part is larger than a height of the module.

[0009] Thus, another object of the invention is to provide a portable communication device solving also this

problem.

[0010] According to a first aspect of the invention, there is provided a portable communication device having a housing, a lens element for responding to an image, and providing an optical image signal, the device comprising:

a camera element, responsive to the optical image signal, wherein the lens element is slidable along an axis, between at least two positions, a first position essentially inside the housing and a second ejected position essentially outside the housing.

[0011] A second aspect of the present invention is directed towards a portable communication device including the features of the first aspect, wherein the lens element in the second ejected position is rotatable around the axis.

[0012] A third aspect of the present invention is directed towards a portable communication device including the features of the first aspect, wherein the lens element in the first position is adapted to respond to images through an opening in a rear-side of the device.

[0013] A fourth aspect of the present invention is directed towards a portable communication device including the features of the first aspect, wherein the lens element is securable in the first position by means of one or more securing elements.

[0014] A fifth aspect of the present invention is directed towards a portable communication device including the features of the first aspect, wherein the securing elements are snap joints.

[0015] A sixth aspect of the present invention is directed towards a portable communication device including the features of the first aspect, wherein the securing element is a ball screw.

[0016] A seventh aspect of the present invention is directed towards a portable communication device including the features of the first aspect, wherein the housing comprises a lens insertion hole provided with guide elements such as guide grooves and/or guide rails.

[0017] An eight aspect of the present invention is directed towards a portable communication device including the features of the first aspect, wherein the lens element comprises two parts, a first part being slidable in the lens insertion hole, and a second part being rotatable around the axis.

[0018] A ninth aspect of the present invention is directed towards a portable communication device including the features of the first aspect, wherein the lens element is spring tensioned.

[0019] A tenth aspect of the present invention is directed towards a portable communication device including the features of the first aspect, wherein a display is adapted to operate as a viewfinder.

[0020] The invention has the following advantages: A built-in camera in a thin portable communication device. This provides better opportunity to design the commu-

nication device in a desired way, for instance to find a place to put it without infringing other parts of the device.

[0021] It should be emphasized that the term "comprises/comprising" when used in this specification is taken to specify the presence of stated features, integers, steps or components, but does not preclude the presence or addition of one or more other features, integers, steps, components or groups thereof.

BRIEF DESCRIPTION OF THE DRAWINGS

[0022] The present invention will now be described in more detail in relation to the enclosed drawings, in which:

Fig. 1 shows a portable communication device provided with a camera, according to an embodiment of the invention, wherein the camera is shown in a so-called "ready to use mode", wherein the camera is fixed to the rear-side and the viewfinder is the display of the device.

Fig. 2 shows the same portable communication device as illustrated in Fig. 1, whereby the camera is shown in an ejected position.

Fig. 3 shows the same portable communication device as in Figs. 1-2, whereby the camera is shown in a position directed to a user of the device.

Fig. 4 is a block diagram of camera circuitry.

DETAILED DESCRIPTION OF EMBODIMENTS

[0023] As required, detailed embodiments of the present invention are disclosed herein; however, it is to be understood that the disclosed embodiments are merely examples of the invention that may be further embodied in various and alternative forms other than described below. The drawings are not necessarily to scale, and some elements may be exaggerated or minimized to show details of particular components or features. Therefore, specific structural and functional details disclosed herein are not to be interpreted as limiting in any sense, but merely as a basis for the claims and as a representative basis for enabling one skilled in the art to variously put the present invention into practice.

[0024] Now is referred to Fig. 1. In Fig. 1 is shown a portable communication device 10, herein a cellular phone in a view from a rear-side thereof 12. The cellular phone 10 comprises a housing 14, provided with a throughgoing hole 16 in the rear-side 12. A lens element 18 having a lens 19 for responding to an optical image is provided, in such a way that the lens 19 can look through the hole 16. This could be provided for instance by the lens element 18 having a rod-like structure being inserted into a lens insertions hole 22, which extends in a direction perpendicular to the hole 16. In this figure,

the lens element 18 is shown in a first position inside and fixed to the housing 14. The cellular phone could be used as a digital camera, whereby typically a display provided on a front side (not shown) of the cellular phone is employed as viewfinder. The cellular phone further includes conventional digital camera circuitry such as memory circuitry etc; however, this will be further described by means of a block schematic below with reference to Fig. 4.

[0025] The lens element could be secured by one or more securing elements (not shown in this figure) such as snap joints, a ball screw or the like. Any suitable securing element may be provided without departing from the invention. Preferably, the securing elements and the hole (for instance depth) is/are adapted to protect the lens well from damage. For instance, additional external distances (not shown) could be provided concentrically to the hole to increase its depth, or suitable cover elements such as lid-like covers may also be employed. Since such covers are well known for a person skilled in the art to design, they are not illustrated in detail in this figure.

[0026] Fig. 2 shows the same cellular phone as in Fig. 1, but with ejected lens element 18 in a second position (also referred to as a "pop-out" position). In this second position, a first part 18a of the lens element 18 has been slid in the lens insertion hole 22, whereby a second part 18b of the lens element, now ejected outside the lens insertion hole 22, is rotatable around an axis 20 extending in the same direction as the lens element 18 ejects. In this second position, it is possible to almost freely rotate the second part 18b of the lens element 18b comprising the lens 19. Preferably, this rotation is up to 180°. However, any degree of rotation is possible if desired without departing from the invention.

Preferably, the lens insertion hole 22 has guide elements, such as guide grooves and/or guide rails. Corresponding grooves and/or rails is then provided at the lens element 18. For instance, the first part 18a of the lens element could be provided with suitable grooves, whereby the second part has guide elements preventing the lens 19 from rotation when pushed into the first position, i. e., preventing the lens 19 from rotating away from the hole 16.

[0027] Fig. 3 shows the same cellular phone as shown in Fig. 1 and 2, whereby the lens 19 is in a position turned to a user of the phone. This figure could represent a situation of video chatting, or when a user takes a photo of himself/herself.

[0028] Preferably, the lens element 18 is provided at the long sides of the phone (as seen by a user looking at the front side 12b comprising a display 24). However, any suitable other position is possible, provided that space requirement and other conventional design parameters are fulfilled. Since the placement of the lens element 18 is obvious for a person skilled in the art to design, this will not be further described.

[0029] Preferably, the view-finder (for previewing im-

ages) is the display 24 of the phone, even if it can be a separate unit, normally since this is a cost efficient solution. By means of the view finder (display) 24 photos taken can be checked before sending them as MMS or e-mail. A photo can also be used to customize the display. Any button 26, or other suitable picture-enabling element could be used to take a picture, or start the camera (including video camera) function of the phone. Enter buttons may also exist to transfer picture data shown in the display 24 into a memory unit (not shown).

[0030] Preferably, the lens element is adapted to be pulled out from the first position to the second position by a user. Therefore, the design of the lens element is preferably adapted to comply with this requirement. Examples may be grip elements or the like.

[0031] Alternatively, the lens element can be spring tensioned, to be able to "pop out" for instance when pushed. Also power operated solutions, such as electrical motor or the like could be employed, provided that power consumption and other requirements are fulfilled.

[0032] Now is referred to Fig. 4 illustrating a simplified block schematic of an example of a camera function, typically for the embodiments of the invention described above.

[0033] An image 101 is directed to the lens 19 within the lens element 18, possibly comprising filter element, whereby the image 101 is transformed into an optical image signal 102. The optical image signal 102 is then further transmitted to a camera module 103, which can be provided inside the housing (not shown) of the cellular phone (not shown) at any proper location thereof. In this block schematic, the camera module 103 communicates with an integrated processor 104 that performs camera control among other tasks. The camera module comprises analogue image processing functions analogue to digital conversions (A/D) and further conventional image processing functions. All these functions, in the following referred to as "camera circuitry", can be provided as a single-chip solution or could be a module solution, whereby separate modules communicate with each other. This will not be further described since this is well known technology for a person skilled in the art. Connections can be any suitable type, including wireless such, for instance Bluetooth™ wireless control, when appropriate.

[0034] The cellular phone can operate as being provided with a still and/or video camera, and it can be adapted for transmitting images, do multimedia messaging, digital postcards etc via communication networks, such as a mobile network.

[0035] The present invention has many advantages, of which several have been mentioned above. Yet another advantage is that the viewfinder (typically the display) and the camera are not firmly arranged to each other, which implies that the "camera" can be operated with great freedom.

[0036] In the embodiments described above, a cellular phone provided with camera has been described,

without any intention to limit the invention to only this type of portable communication device. Instead, the invention is directed to cover any such device.

[0037] The term "portable communication device" includes portable radio communication equipment such as a cellular phone, a smart phone, a pager, cordless phone, a communication module, a PDA or any other type of portable device communicating with radio waves. Most likely, there will be a number of varying portable communication devices in the future when the 3rd generation cellular systems are implemented.

[0038] The present invention has many advantages such as: light weight, damage protected digital camera, always ready to use, no external equipment to snap on before taken a picture.

[0039] The foregoing has described the principles, preferred embodiments and modes of operation of the present invention. However, the invention should not be construed as being limited to the particular embodiments discussed above.

[0040] Thus, the above-described embodiments should be regarded as illustrative rather than restrictive, and it should be appreciated that variations may be made in those embodiments by workers skilled in the art without departing from the scope of the present invention as defined by the following claims.

Claims

1. A portable communication device having a housing (14), a lens element (18) for responding to an image (101), and providing an optical image signal (102), the device (10) comprising:
a camera element (103), responsive to the optical image signal (102), wherein the lens element (18) is slidable along an axis (20), between at least two positions, a first position essentially inside the housing and a second ejected position essentially outside the housing (14).
2. A portable communication device according to claim 1, wherein the lens element (18) in the second ejected position is rotatable around the axis (20).
3. A portable communication device according to claim 1, wherein the lens element (18) in the first position is adapted to respond to images (101) through an opening (16) in a rear-side (12) of the device (10).
4. A portable communication device according to any one of the claims 1-3, wherein the lens element (18) is securable in the first position by means of one or more securing elements.

5. A portable communication device according to claim 4, wherein the securing elements are snap joints.
6. A portable communication device according to claim 4, wherein the securing element is a ball screw. 5
7. A portable communication device according to any one of the claims 1-5, wherein the housing (14) comprises a lens insertion hole (22) provided with guide elements such as guide grooves and/or guide rails. 10
8. A portable communication device according to claim 7, wherein the lens element (18) comprises two parts, a first part (18a) being slidable in the lens insertion hole (22), and a second part (18b) being rotatable around the axis (20). 15 20
9. A portable communication device according to any one of the claims 1-8, wherein the lens element (18) is spring tensioned.
10. A portable communication device according to any one of the claims 1-9, comprising a display (24) adapted to operate as a viewfinder. 25

30

35

40

45

50

55




Fig. 1.




Fig. 2




Fig. 3




Fig. 4



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 02 02 7796

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	EP 0 930 770 A (MITSUBISHI ELECTRIC CORP) 21 July 1999 (1999-07-21) * page 5, column 8, line 19 - page 6, column 9, line 59 * * figures 5,6 *	1-5,7-10	H04N1/00 H04N7/14
A	WO 01 39497 A (ORANGE PERSONAL COMM SERVICES ; FISHER GRAHAM (GB)) 31 May 2001 (2001-05-31) * figures 2,3 * -----	1-10	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			H04N
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 16 May 2003	Examiner Van der Zaai, R
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 (03.02) (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 02 02 7796

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

16-05-2003

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0930770 A	21-07-1999	JP 11205761 A	30-07-1999
		EP 0930770 A2	21-07-1999

WO 0139497 A	31-05-2001	GB 2358538 A	25-07-2001
		AU 1535901 A	04-06-2001
		CA 2391994 A1	31-05-2001
		CN 1399844 T	26-02-2003
		EP 1234448 A1	28-08-2002
		WO 0139497 A1	31-05-2001

EPO FORM P0469

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

THIS PAGE BLANK (USPTO)

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)